

**FOR YOUR
LUXURY
HOUSE**

**✓ TRUSTED
EVERYWHERE**



Faster Charging



Life Saver



Pure Sinewave





FEATURES

- Powerfull micro controller based PWM technology
- Advanced fuzzy logic control technology reduces frequency of water topping in battery
- Minimum loss of energy while converting DC to AC
- Noiseless Operation
- Keeps voltage within safe range



TECHNICAL SPECIFICATIONS*

Model	2KVA	2.5KVA	3.2KVA
I/P Range(Normal mode)		110V-290V ± 10V	
I/P Range(UPS mode)		175V-265V ± 5V	
O/P Voltage Battery Mode		225V ± 5V	
O/P Frequency Battery Mode		50HZ ± 0.5HZ	
O/P Waveform Battery Mode		Sinewave	
Low Battery Shutdown		20.8V ± 0.2V	20.8V ± 0.4V
Running Load	64A±2AMP	84A±2AMP	100A±2A
Overload	64A±2AMP		55A±2A
DC Voltage	24V	24V	24
Charging Current	11A±2A		11A±2A
Charging Cut off	28.6V ± 0.2V	28.6V ± 0.2V	28.6V ± 0.2V
No Load Current		<2.5A	
Battery Recommended		135AH-250AH	

*Specifications may change due to continuous improvement



Allied Power Solar Solutions

C-67, Hind Vihar, Prem Nagar-3, Kirari, New Delhi-110086, INDIA

+91 9117902634 alliedpowersolar@gmail.com

(GOVT. RECOGNISED EXPORT HOUSE)